Dixon In-Line Lubricators

Designed for use with hose-connected tools that are too far from the compressor to be lubricated by a permanently mounted unit.



- The minimum flow rate that must be achieved for the PL series lubricators to work is 30 SCFM. A flow rate less than 30 SCFM will not create the pressure difference needed between chambers to force the oil into the air stream.
- Install within 25 feet of the air tool requiring lubrication. Refer to the arrow for proper air flow direction.
- transparent sight disc allows visual inspection of oil level
- oil flow regulated by screwdriver adjustment of oil adjustment valve inside body
- not recommended for constant flow applications
- for use on reciprocating tools only
- · can dispense standard air tool lubricant or Dixon anti-freeze lubricant
- lubricator body is 356-T6 aluminum

Description:

• The lubricator has two reservoirs. The upper reservoir holds the oil, and a lower reservoir that is the passageway for the air to enter. The air and oil mixture exits through the lower reservoir. The oil adjustment valve between the two compartments initially allows air to enter the reservoir to pressurize it, and then it controls the amount of oil entering the air stream.

How it works:

⁹ Before the hose is charged with air, the pressure in both chambers of the lubricator are equal. When the tool is turned on it draws air from the compressor through the lower chamber. As air passes through the lower chamber it creates an area of low pressure. When the pressure in the lower chamber is less than the pressure in the upper chamber the dual purpose oil adjustment valve allows oil to flow at the set rate into the airstream of the chamber below to lubricate the tool. When the flow of air stops, the oil adjustment valve allows pressure to build in the top chamber until the pressure is equal between the top and bottom. As long as the pressure in the upper chamber no oil will flow through the oil adjustment valve.

Note: These lubricators are only recommended for use with tools that are frequently turned on and off.



Installation:

- At start up, additional lubricant is required to coat the inside of the line between the lubricator and the tool.
- To avoid operating a dry tool, add 1/2 ounce (15cc) of oil directly into the line.
- By removing the fill plug and using a screwdriver, the operator can adjust the amount of oil flowing into the air stream. It is not necessary to shut off the airflow to do this.
- The viscosity of the oil used and uniqueness of the application determine the right setting for proper lubrication.
 A setting of 5 is suitable for average conditions using 10-weight oil. Remember that the lag time between adjustment and resulting effect at the tool may be as long as an hour. Make small adjustments, and check the result.

Storage:

• The simple principle behind the operation of this lubricator does not provide for oil shut off when the tool is not being used. To prevent a pressure differential from forcing the remaining oil from the reservoir into the air line, turn the lubricator upside down or open the fill plug to depressurize the reservoir.

Safety Notes:

- Wear eye protection when connecting or disconnecting couplings. Always use a whip hose with impact tools, King Cable to protect junctions, and couplings that are compatible with the media being transferred.
- Always unscrew fill plug slowly to depressurize upper chamber before filling or adjusting valve.

IN-LINE LUBRICATOR



NPT Sizes	Part #	Oil Capacity	Max. Working Pressure	Air Flow at 70 PSI	Length A	Width B	Height C	Weight
1⁄2"	PL300	1.4 fluid ozs.	500 PSI	30 SCFM	41⁄2"	2¼"	21⁄4"	14 ozs.
3/4"	PL400	3.7 fluid ozs.	200 PSI	70 SCFM	6"	2¾"	2¾"	22 ozs.
3⁄4"	PL400L	11.0 fluid ozs.	300 PSI	70 SCFM	7"	31⁄2"	3¾"	38 ozs.
1"	PL500	16.0 fluid ozs.	250 PSI	100 SCFM	10"	4¼"	4"	69 ozs.

Available with Filter

Combination unit consists of 9076M particle filter with 40 micron sintered bronze element and PL400 (3.7 ounce) or PL400L (11.0 ounce) lubricator.

Part #	Max. WP		
PL400WF	200 PSI		
PL400LWF	300 PSI		

Repair Parts (same for all sizes)				
Description	Part #			
(A) oil adjustment valve assembly	851661			
(B) valve gasket	452531			
(C) fill plug	452525			
(D) fill plug O-ring	844319			
(E) sight disk	452532			
(F) sight disk seal	847272			
(G) sight disk lock nut	452533			



Type of oil to use:

Any petroleum-base, non-detergent light weight oil (SAE 10/150SSU) which will readily break up into a mist,

i.e., Mobil DTE light or comparable oil. *Do not use any* synthetic oil or oils containing additives or solvents. SAFETY

Lub	oricant		Anti-Freeze		
Part #	Size	Pkg. Qty.	Part #	Size	Pkg. Qty.
DATL016	1 pint	12	DATL016W	1 pint	12
DATL128	1 gallon	4	DATL128W	1 gallon	4

· Base can be fitted to any existing PL lubricator, keeps lubricator from flipping or rolling over, ensuring that it provides continuous lubrication to the downstream air tool.

Description	<i>Aluminum</i> Part #		
leveling base for PL300	LB300		
leveling base for PL400	LB400		
leveling base for PL500	LB500		



In-Line Lubricator Base

877.963.4966

